

## WRG WINSTON / ROYAL GUARD CORPORATION

## Strainer **Inquiry Questionnaire**

(Please fill in as much as possible)

Company	Date
Address	Phone
	Fax
Name	F:
Title or Dept	
Quantity: Winston Type:	Style:
Nozzle size and flange rating:	#( ) RF ( ) RTJ ( )ANSI
( ) Flanged both inlet and outlet nozzles (	) Butt weld inlet and outlet nozzles
( )	
( ) Liquid: Flow	w: GPM PPH Viscosity
( ) Gas ( ) Steam ( ) Air Flow:	SCFMSCFHSCFD
<u> </u>	ACFM
Molecular Weight Specific Gravit Operating pressure: PSIG Te	.y Density
Operating pressure:PSIG Tell	mperature: °F,
DESIGNPSIG & °F. C.A	A
	PSI (Clean)PSI (Dirty)
-	or vapor will require the operating pressure, temperature
and density, or specific gravity of the process	
Cover: ( ) Bolted ( ) Quick-opening	
( ) Lifting lug ( ) Davit ( ) Other	
Size of solids to strain	( ) Periorated basket with
wire mesh to strain and with perforated	
Materials of construction:	i support.
Body: ( ) Carbon steel ( ) Other	
Basket: ( ) 304 S.S. ( ) Other	
Other fittings required:	
Special Requirements:	
	on VIII Division 1 Code stamped ( ) yes ( ) no
	on VIII, Division 1Code stamped ( ) yes ( ) no.
	B ( ) ASME B31.4 ( ) ASME B31.12
	B Design factor (0.5 is the most common)
( )	( ) None
Radiography ( ) Yes (	) No
NDE (UT, MT, PT, ETC.) ( ) Yes (	) No
PWHT ( ) Yes (	) No
Painting ( ) Yes (	) No
Misc. ( ) Yes (	) No
141136. ( ) 163 (	) INO