

WINSTON / ROYAL GUARD CORPORATION Separator Cartridge

WCT6--P Series

WCT6--P series separator cartridges are furnished in the type 62 Liquid-Liquid Coalescer Separator for the separation of two immiscible liquids. The separator filter is hydrophobic allowing oil to pass through while repelling water. It is used as the second stage in conjunction with the first stage WCT6--R coalescing cartridge.



FOR TYPE 62-CC-2S LIQUID-LIQUID

COALESCER SEPARATORS

The media is treated cellulose and pleated for maximum surface area. The pleated media is supported by a galvanized or tin plated perforated metal core. A galvanized or tin plated metal end cap with bolt hole can cover one end as required for installation.

BENEFITS:

- Low pressure drop.
- Pleated design offers efficiency at an economical cost.

OPERATION SPECIFICATIONS:

- Flow direction is outside to in.
- Micron rating: 5
- PH range: 5 9
- Recommended differential pressure for element change-out: 15 P.S.I.
- Recommended maximum operating temperature: 240 ° F.
- Buna-N Gaskets are standard.
- Galvanized or tin plated end cap and core.

STANDARD PART NUMBERS AND DIMENSIONS:

- WCT611P......6" O.D -- 11-1/4" Long -- 3-1/2" I.D.
- WCT614P......6" O.D -- 14-1/2" Long -- 3-1/2" I.D.
- WCT616P......6" O.D -- 16-1/4" Long -- 3-1/2" I.D.
- WCT622P......6" O.D -- 22-1/4" Long -- 3-1/2" I.D.
- WCT628P.......6" O.D 28-3/4" Long -- 3-1/2" I.D.
- WCT633P......6" O.D 33-1/4" Long -- 3-1/2" I.D.
- WCT636P......6" O.D 36" Long -- 3-1/2" I.D.
- WCT640P......6" O.D 40" Long -- 3-1/2" I.D.
- WCT644P......6" O.D 44" Long -- 3-1/2" I.D.
- WCT648P.......6" O.D 48" Long -- 3-1/2" I.D.
- WCT656P.......6" O.D 56" Long -- 3-1/2" I.D.

Specifications are subject to change without notice. 4-20-2021 (supersedes 9-21-2018)

WINSTON / ROYAL GUARD CORPORATION

P. O. Box 1145 ● White Oak, Texas 75693 USA Phone (800) 527-8465 ● (903) 757-7341 ● Fax (903) 759-6986 Winston-RoyalGuard.com ● e-mail: sales@winston-royalguard.com Copyright © 2021 Winston/Royal Guard Corporation. All rights reserved